

Technical table argesystems back gauges

| ARGESYSTEMS MODEL | TON. | BACK GAUGE LENGTHS | | APPLICATION - FIXING | | | X - AXIS SROKE | | | | | R - AXIS SROKE | | | | | Z - AXIS SROKE | | X5 X6 - AXIS SROKE | | MANAGEABLE AXES | | | | | | | | |
|-------------------|-----------------|------------------------|--------------|----------------------|---------|-----------|----------------|--------------|-----|----------|----------------|-----------------------|--------------|-----|----------|----------------|-----------------------|----------------|-----------------------|----------|-----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| | | RECOMMENDED UP TO TON. | MINIMUM BEAM | MAXIMUM BEAM | ON FRME | ON SQUARE | ON BASES | 600 STANDARD | 800 | 1000 | SPEED 3000 rpm | MECHANICAL RESOLUTION | 150 STANDARD | 200 | 250 | SPEED 3000 rpm | MECHANICAL RESOLUTION | SPEED 3000 rpm | MECHANICAL RESOLUTION | STROKE | SPEED 3000 rpm | SPEED 3000 rpm | SPEED 3000 rpm | SPEED 3000 rpm | SPEED 3000 rpm | SPEED 3000 rpm | SPEED 3000 rpm | SPEED 3000 rpm | SPEED 3000 rpm |
| M 1 | 50 t | 800 | 1500 | ✗ | ✓ | ✗ | ✓ | ✗ | ✗ | 500 mm/s | ± 0,05 | ✓ | ✓ | ✗ | 125 mm/s | ± 0,05 | 1400 mm/s | ± 0,1 | ± 140 mm | 150 mm/s | ✓ | ✗ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✗ |
| M 2 | 250 t | 1500 | 3500 | ✓ | ✓ | ✗ | ✓ | ✓ | ✓ | 565 mm/s | ± 0,05 | 150 MANUAL | | | | | ✗ | ✗ | ✗ | ✗ | ✓ | ✓ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ |
| M 3 | 250 t | 1500 | 3500 | ✓ | ✓ | ✗ | ✓ | ✓ | ✓ | 565 mm/s | ± 0,05 | ✓ | ✓ | ✓ | 130 mm/s | ± 0,05 | 1400 mm/s | ± 0,1 | ± 150 mm | 150 mm/s | ✗ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| M 3 basic | 250 t | 1500 | 3500 | ✓ | ✓ | ✗ | ✓ | ✓ | ✓ | 565 mm/s | ± 0,05 | ✓ | ✗ | ✗ | 130 mm/s | ± 0,05 | 1400 mm/s | ± 0,1 | NOT AVAILABLE | | ✗ | ✓ | ✓ | ✓ | ✗ | ✗ | ✗ | ✗ | |
| M 5 | > 250 t - 500 t | 2500 | 6000 | ✓ max 3500 | ✓ | ✗ | ✗ | ✓ | ✓ | 380 mm/s | ± 0,05 | ✗ | ✓ | ✓ | 130 mm/s | ± 0,05 | 1400 mm/s | ± 0,1 | ± 150 mm | 150 mm/s | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| M 6 | 250 t | 2000 | 4500 | ✗ | ✗ | ✓ | ✗ | ✓ | ✓ | 460 mm/s | ± 0,05 | ✓ | ✓ | ✗ | 120 mm/s | ± 0,05 | 1400 mm/s | ± 0,1 | ± 150 mm | 150 mm/s | ✗ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| M 6P | > 250 t - 400 t | 2000 | 4500 | ✗ | ✗ | ✓ | ✗ | ✓ | ✓ | 365 mm/s | ± 0,05 | ✓ | ✓ | ✗ | 120 mm/s | ± 0,05 | 1400 mm/s | ± 0,1 | ± 150 mm | 150 mm/s | ✗ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| M 7 | > 400 t - 800t | 2500 | 8000 | ✗ | ✓ | ✗ | ✗ | ✓ | ✓ | 350 mm/s | ± 0,05 | ✗ | ✓ | ✓ | 120 mm/s | ± 0,05 | 1400 mm/s | ± 0,1 | ± 150 mm | 150 mm/s | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| M 8 | 50 t | 2000 | 6000 | ✗ | ✗ | ✓ | ✗ | ✓ | ✓ | 600 mm/s | ± 0,05 | ✗ | ✓ | ✓ | 200 mm/s | ± 0,05 | 125 mm/s | ± 0,1 | NOT AVAILABLE | | NOT AVAILABLE | | | | | | | | ✓ |